

Manually operated high press' grease pump 20-kg-BE-Ø 270-310 mm

Item number: EAN: Discount group:

Technical data Pumping media: Delivery rate/stroke (cm³): Discharge hose:

Grease supply: Follower plate: Ø follower plate (mm): Length of suction tube (mm): Discharge pressure up to (bar): Material pump body: Material pump head: Surface treatment: Lacquering dust cover: lubricating greases, up to NLGI 2 3,8 high pressure hose, 11 x 1500 mm (12 765 601) manually lever operated for 20 kg container 270 – 310 475 200 steel - NFA 35-561 impact-resistant zinc die casting all steel components are galvanized blue, Pantone 294 C

Specification

- Manual pump for grease supply
- Pump
- Suction tube
- Dust cover (17 176), stabilising-fixing bracket (17 197) and follower plate (17 300)

17 694

А

4103810176944

- High pressure grease hose, 11 x 1500 mm (12 765 601)
- Spout, angled, G 1/8", 150 mm (12 735)
- Coupler, 4 jaws, G 1/8" (12 731)
- Robust carrying handle
- Packed in single carton box

Packaging

Dimensions packaging LxWxH (mm):670 x 420 x 100Weight including package (kg):6,07Packing unit:1,0

No issue of guarantee for the data.